

CP-LNC-FL20-120

Floodlight Camera

- 1/2.7" 2MP Progressive Scan CMOS
- Max 25fps@1080P
- H.264 and MJPEG stream encoding
- Built-in Speaker and Built-in Microphone
- 2.3mm lens
- Indoor: IR Range of 10 meters, Outdoor: 20 meters, Memory Card
- Mobile Software: Android, iOS



About CP PLUS

The brand that is on its way to lead the world when it comes to the security and surveillance industry, CP PLUS, keeps bombarding the market with the most reliable range of products that have been designed carefully and methodically to automate the whole surveillance and security process, no matter how big your premises are.

It was the initiative to help the public in the area where they are the most vulnerable and to empower the sense of safety in our hearts that had conceptualized CP PLUS. And embarking on its mission to make the world a safer and more secure place has taken the brand's journey to unprecedented levels even when compared to international competitors.



CP-LNC-FL20-120

Floodlight Camera

Feature	Specification
Image Sensor	1/2.7" 2MP Progressive Scan CMOS
Minimum Illumination	0.3Lux
Wattage	16W
CCT	3000K
Lumens	1200
Lifetime (hours)	20,000
White Balance	Auto/Manual
Gain Control (AGC)	Auto/Manual
Lens	2.3mm
Back Light Compensation	Auto/Manual
Video Compression	H.264/MJPEG
DNR	3D-DNR
Angle of View	120°
Video Streaming	25fps(Max)
Resolution	1920x1080, 1280x720
ICR	ICR infrared filter functional within 15 meters distance
Audio Compression	G.711/G.726
Audio	Built-in Speaker & Built-in Microphone
Bit Rate	64kbps-4Mbps
PIR Detection	120°
Micro SD Card	Max.128GB
Wi-Fi	WiFi802.11 b/g/n Wi-Fi connection @ 2.4GHz only
Wireless Frequency	2.4 GHz ~ 2.4835 GHz
Protocol	TCP/IP, HTTP, TCP, ICMP, UDP, ARP, IGMP, SMTP, FTP, DHCP, DNS, DDNS, NTP, UPNP, RTSP, ONVIF etc

Feature	Specification
Security	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK, WPS
Smart Phone	iPhone, iPad, Android Phone
IR	Outdoor: 20 meters, indoor: 10 meters (sensitive to environmental change)
Siren	Remote-activated 110-decibel alarm
Operating Temperature	-28°C to 65°C/Weather-resistant
Power Source	110-260V
Power Consumption	1.5-3W (Camera running all functions)
Mounting Base	4¾-inch (12.065-cm) diameter
Dimension	280 x 130 x 130 mm
Weight	1.4 KG